



HomePlug Ethernet Bridge 1 x RJ-45 Port / 1 x HomePlug Port

HP-8500

✓ RoHS Compliant

Taiwan / Headquarters

Edimax Technology Co., LTD.
TEL:886-2-7739-6888
FAX:886-2-7739-6887
sales@edimax.com.tw

China

Beijing Edimax Science &
Technology Co., LTD.
TEL:8610-6213-9288
FAX:8610-6213-9231
sales@edimax.com.cn

Europe

Edimax Technology Europe B.V.
TEL:31-499-377344
FAX:31-499-372647
sales@edimax.nl

Latin America

TEL:1-786-845-8099
FAX:1-786-331-8490
sales_latinamerica@edimax.com

Poland

Edimax Technology Europe
B.V. SP. Z O.O.
Tel: +48(22)-6060-255
Fax: +48(22)-6060-254
sales@edimax.nl

U.S.A.

Edimax Computer Company
TEL:1-408-496-1105
FAX:1-408-980-1530
sales@edimax.com

U.K.

Edimax Technology (UK) Ltd.
TEL:44-870-7740226
FAX:44-870-7740227
info@edimax.co.uk

Specification

- Computer Interface : IEEE 802.3 / 802.3u
- Network Ports : 85 Mbps Powerline port / 10BASE-T / 100BASE-TX Ethernet port
- Network Interface : HomePlug Powerline
- Cable Connection : 10BASE-T: UTP CAT.3,4,5 / 100Base-TX: UTP CAT.5 / Powerline: No New Wires
- Installation : Plug-and-Play
- Modulation Schemes : OFDM Symbol Modulation DQAM 256/64/16 / QPSK, DBPSK, ROBO Carrier Modulation
- Additional Protocols : Forward Error Correction (FEC) / Automatic channel adaptation
- Quality of Service (QoS) : Integrated Quality of Service (QoS) features / such as prioritized random access / contention-free access, and segment bursting
- Additional Features : "Boot From Host" and "Field-Upgradeable Firmware"
- LED Indicators : PWR (Power) / HP (Powerline Activity) / ETH (Ethernet Activity)
- Operating Temperature : 0°C– 40°C (32 to 104°F)
- Humidity : 5% - 90%

Model NO.	HP-8500
Standards	HomePlug 1.0 compatible
Network Ports	85Mbps Powerline
Frequency Band	4.3 MHz ~ 20.9 MHz
Power	100 to 240v @ 50/60 Hz Internal
Dimension	4.5 x 3.0 x 1.0 inches
Certification	FCC Class B, CE Mark, HomePlug Configuration
OS Supports	Windows 98SE, Me, 2000 and XP

